# Safety Data Sheet Fly Ash

#### **Section 1. Identification**

GHS product identifier: Fly Ash

Chemical name: Calcium compounds, calcium silicate compounds, and other calcium compounds containing

iron and aluminum make up the majority of this product.

Other means of identification: Coal As

Relevant identified uses of the substance

or mixture and uses advised against: Building materials, construction, a basic ingredient in concrete.

Supplier's details: 300 E. John Carpenter Freeway, Suite 1645

Irving, TX 75062 (972) 653-5500

Emergency telephone number (24

hours):

CHEMTREC: (800) 424-9300

#### **Section 2. Hazards Identification**

OSHA/HCS status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the CARCINOGENICITY – Category 1A; H350

substance or mixture: SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) – Category 3; H335

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1; H372

SKIN CORROSION/IRRITATION - Category 2; H315

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1; H318

#### GHS label elements

Hazard pictograms:







Signal word: Danger

**Hazard statements:** Causes severe skin burns and eye damage.

May cause an allergic skin reaction. May cause respiratory irritation.

May cause cancer.

**Precautionary statements:**Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Use outdoors in a well ventilated area. Wash any

expected hody parts the urguighty after headling. Wear protective alexes (protective

exposed body parts thouroughly after handling. Wear protective gloves/protective

clothing/eye protection/face protection. Contaminated clothing must not be allowed out of the

workplace.

If exposed or concerned: Immediately get medical advice/attention if you feel unwell or

irritation or rash occurs.If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse continuously with water for several minutes. Remove contact lenses, if present and easy to do.If inhaled: Remove person to fresh air and

Storage: keep comfortable for breathing. If swallowed: Rinse mouth. Do not induce vomiting.

Restrict or control access to stockpile areas (store locked up). Engulfment hazard: To prevent burial or suffocation, do not enter a confined space, such as a silo, bulk truck or other storage container or vessel that stores or contains fly ash without an effective procedure for assuring

safety. Store in a well ventilated area. Keep container tightly closed.

Disposal: Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazards not otherwise classified

(HNOC):

Response:

None known



Supplemental Information:

Respirable Crystalline Silica (RCS) may cause cancer. Repeated inhalation of respirable crystalline silica (quartz) may cause lung cancer according to IARC and NTP; ACGIH states that it is a suspected cause of cancer. Other forms of RCS (e.g., tridymite and cristobalite) may also be present or formed under certain industrial processes.

# Section 3. Composition/information on ingredients

Substance/mixture:

Mixture

**Chemical Name:** 

Calcium compounds, calcium silicate compounds, and other calcium compounds containing

iron and aluminum make up the majority of this product.

#### CAS number/other identifiers

Ingredient name	%	CAS number
Fly Ash	100%	68131-74-8
The structure of Fly Ash may contain the following in some concentration ranges:		
Calcium oxide	0-5	1305-78-8
Quartz	0-0.1	14808-60-7
Magnesium oxide	0-4	1309-48-4
Magnesium oxides are not classifiable as a hazard under Title 29 <u>Code of Federal Regulations</u> 1910.1200.		

Any concentration shown as a range is to protect confidentiality or is due to process variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First aid measures

#### Description of necessary first aid measures

**Eye Contact:** 

Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least

20 minutes. Chemical burns must be treated promptly by a physician.

Inhalation:

Seek medical help if coughing or other symptoms persist. Inhalation of large amounts of fly ash requires immediate medical attention. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position

comfortable for breathing. If the individual is not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in a recovery position and get medical attention immediately. Maintain an

open airway.

Skin Contact:

Get medical attention immediately. Quickly remove contaminated clothing, shoes, and leather goods such as watchbands and belts. Quickly and gently blot or brush away excess fly ash. Immediately wash thoroughly with lukewarm, gently flowing water and non-abrasive pH natural soap. Seek medical attention for rashes, burns, irritation, dermatitis and prolonged unprotected exposure to wet fly ash, fly ash mixtures or liquids from wet fly ash. Burns should be treated as caustic burns. Discomfort or pain cannot be relied upon to alert a person to a serious injury. You may not feel pain or the severity of the burn until hours after the exposure Chemical burns must be treated promptly by a

physician. In the event of any complaints or symptoms, avoid further exposure.

Ingestion:

Get medical attention immediately. Call a poison center or physician. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING unless directed to do so by medical personnel. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Have victim drink 60 to 240 mL (2 to 8 oz.) of water. Stop giving water if the exposed person feels sick as vomiting may be dangerous. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.



# Most important symptoms/effects, acute and delayed potential acute health effects

Eve contact: Causes serious eye damage. Inhalation: May cause respiratory irritation.

Skin contact: Causes severe burns.

Ingestion: May cause burns to mouth, throat and stomach.

## Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following: pain, watering and redness.

Inhalation: Adverse symptoms may include the following: respiratory tract irritation and coughing. Skin contact: Adverse symptoms may include the following: pain or irritation, redness and blistering may

occur, skin burns, ulceration and necrosis may occur.

Ingestion: Adverse symptoms may include the following: stomach pains.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large quantities

have been ingested or inhaled.

Specific treatments: Not applicable.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. It may be

dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# **Section 5. Fire-fighting measures**

# Extinguishing media

Suitable extinguishing media: Use an extinguishing agent suitable for the surrounding fire. Unsuitable extinguishing media: Do not use water jet or water-based fire extinguishers.

Specific hazards arising from the

chemical:

Hazardous thermal decomposition

Products: Special protective actions for fire-

fighters: Special protective equipment for fire-

fighters:

Decomposition products may include the following materials: carbon dioxide, carbon

monoxide, sulfur oxides and metal oxide/oxides.

Move containers from fire area if this can be done without risk. Use water spray to keep fire-

exposed containers cool.

No specific fire or explosion hazard.

Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

#### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training. Keep For non-emergency personnel:

> unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe dust. Provide adequate ventilation. Wear appropriate respirator when

ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: For personal protective clothing requirements, please see Section 8.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. **Environmental precautions:** Inform the relevant authorities if the product has entered the environment, including waterways,

soil or air. Materials can enter waterways through drainage systems.

#### Methods and materials for containment and cleaning up

Small spill: Move containers from spill area, Avoid dust generation, Do not dry sweep, Vacuum dust with

equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of waste material by using a licensed

waste disposal contractor.

Large spill:

Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place dust in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Large spills to waterways may be hazardous due to alkalinity of the product. Dispose of waste material using a licensed waste disposal contractor. Note: see section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures: Put on appropriate personal protective equipment (see Section 8). Persons with a

history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure by obtaining and following special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe dust. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material and keep the container tightly closed when not in use. Empty containers retain

product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating,

> drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene

Conditions for safe storage, including any

incompatibilities:

A key to using the product safely requires the user to recognize that fly ash reacts chemically with water to produce calcium hydroxide which can cause severe chemical burns. Every attempt should be made to avoid skin and eye contact with fly ash. Do not get fly ash inside boots, shoes or gloves. Do not allow wet, saturated clothing to remain against the skin. Promptly remove clothing and shoes that are dusty or wet with fly ash mixtures. Launder/clean clothing and shoes before reuse. Do not enter a confined space that stores or contains fly ash unless appropriate procedures and protection are available. Fly ash can build up or adhere to the walls of a confined space and then release or fall suddenly (engulfment).

# Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
Particulates not otherwise classified (CAS SEQ250)	ACGIH TLV (United States, Canada) TWA: 3 mg/m³. Form: Respirable particles TWA: 10 mg/m³. Form: Inhalable particles OSHA PEL (United States) PEL: 5 mg/m³. Form: Respirable fraction PEL: 15 mg/m³. Form: Total dust MSHA PEL (United States) PEL: 5 mg/m³. Form: Respirable fraction PEL: 10 mg/m³. Form: Total dust
Fly Ash	Not Established
Calcium oxide	ACGIH TLV (United States and Canada) TWA: 2 mg/m³ 8 hours OSHA/MSHA PEL (United States) TWA: 5 mg/m³ 8 hours.
Magnesium oxide	ACGIH TLV (United States and Canada) TWA: 10 mg/m³ 8 hours. Form: Inhalable fraction OSHA PEL (United States) TWA: 15 mg/m³ 8 hours. Form: Total particulates
Crystalline Silica (Quartz) (CAS 14808-60-7)	ACGIH TLV (United States) TWA: 0.025 mg/m³. Form: Respirable fraction OSHA PEL (United States) TWA: 0.05 mg/m³. Form: Respirable MSHA PEL (United States) TWA: 10/(%SiO2 + 2) in mg/m3 Provincial Exposure Limits (Canada, various)  ■ Alberta (OHS Code)

0.025 mg/m3 8 hour TWA

- British Columbia (WorkSafeBC OHS Regulation) 0.025 mg/m3 8 hour TWA
- British Columbia (Health, Safety & Reclamation Code, Mines Act) 0.1 mg/m3 8 hour TWA
- Manitoba (Workplace Safety and Health Regulation) 0.025 mg/m<sup>3</sup> 8 hour TWA
- **New Brunswick**
- 0.025 ma/m3 8 hour TWA
- Newfoundland
  - 0.025 mg/m3 8 hour TWA
- **Nova Scotia** 
  - 0.025 mg/m3 8 hour TWA
- Ontario (O. Reg 490/09; and O. Reg. 833)
- 0.1 mg/m3 8 hour TWA
- Prince Edward Island 0.025 mg/m3 8 hour TWA
- Quebec (Regulation Respecting OHS, Chapter S-2.1, r. 13) 0.1 mg/m<sup>3</sup> 8 hour TWA
- Saskatchewan (OHS Regulations)

0.05 mg/m<sup>3</sup> 8 hour TWA

Appropriate engineering controls:

Use only with adequate ventilation. If user operations generate dust, use process enclosures,

local exhaust ventilation or other engineering controls to keep worker exposure to airborne

contaminants below any recommended or statutory limits.

Emissions from ventilation or work process equipment should be checked to ensure they

comply with the requirements of environmental protection legislation.

**Exposure guidelines:** 

**Environmental exposure controls:** 

OSHA PELs, MSHA PELs, Canadian Provincial OELs, and ACGIH TLVs are 8-hr TWA values. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Terms including "Particulates Not Otherwise Classified," "Particulates Not Otherwise Regulated," Particulates Not Otherwise Specified," and "Inert or Nuisance Due" are often used interchangeably; however, the user should review each agency's

terminology for differences in meanings.

## Individual protection measures

Hygiene measures: Clean water should always be readily available for skin and (emergency) eye washing. Periodically

wash areas contacted by material with a pH neutral soap and clean, uncontaminated water. If clothing becomes saturated with material, garments should be removed and replaced with clean, dry clothing. To prevent eye contact, wear safety glasses with side shields, safety goggles or face shields when

Eye/face protection:

handling dust or wet fly ash. Wearing contact lenses when working with fly ash is not recommended.

#### Skin protection

Hand protection: Use impervious, waterproof, abrasion and alkali-resistant gloves. Do not rely on barrier creams in

place of impervious gloves. Do not get material inside gloves.

**Body protection:** Use impervious, waterproof, abrasion and alkali-resistant boots and protective long-sleeved and long-

legged clothing to protect the skin from contact with wet material. To reduce foot and ankle exposure, wear impervious boots that are high enough to prevent material from getting inside them. Do not get material inside boots, shoes, or gloves. Remove clothing and protective equipment that becomes

saturated with material and immediately wash exposed areas of the body.

Appropriate footwear and any additional skin protection measures should be selected based on the Other skin protection:

task being performed and the risks involved.

Use properly fitted, particulate filter respirator complying with an approved standard if a risk Respiratory protection:

assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product, and assigned protection factor of the selected respirator.



# Section 9. Physical and chemical properties

#### **Appearance**

pH:

Physical State: Solid. [Powder] Lower and Upper explosive flammable Not applicable

limits

Color:Gray or whiteVapor pressure:Not applicableOdor:OdorlessVapor density:Not applicableOdor threshold:Not availableRelative density:2.3 to 3.1

>11.5 [Conc. (% w/w): 1%] Solubility: Slightly soluble in water

Melting point: Not available Solubility in water: 0.1 to 1%

**Boiling point:** >1000°C (>1832°F) **Partition coefficient: n-octanol/water:** Not applicable **Flash point:** Not flammable. Not combustible **Auto-ignition temperature:** Not applicable

Flash point:Not flammable. Not combustibleAuto-ignition temperature:Not applicableBurning time:Not availableDecomposition temperature:Not availableBurning rate:Not availableSADT:Not availableEvaporation Rate:Not applicableViscosity:Not applicableFlammability (solid, gas):Not applicable

## Section 10. Stability and reactivity

**Reactivity:** Reacts slowly with water forming hydrated compounds, releasing heat and producing a strong

alkaline solution until reaction is substantially complete.

Chemical Stability: The product is stable.

Possibility of hazardous reactions: Under normal circumstances of storage and use, hazardous reactions will not occur.

Conditions to avoid: No specific data.

**Incompatible materials:** Reactive or incompatible with the following materials: oxidizing materials, acids, aluminum and

ammonium salt. Fly ash is highly alkaline and will react with acids to produce a violent, heat-generating reaction. Toxic gases or vapors may be given off depending on the acid involved. Reacts with acids, aluminum metals and ammonium salts. Aluminum powder and other alkali and alkaline earth elements will react in wet mortar or concrete, liberating hydrogen gas. Limestone ignites on contact with fluorine and is incompatible with acids, alum, ammonium salts, and magnesium. Silica reacts violently with powerful oxidizing agents such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride yielding possible fire and/or explosions. Silicates dissolve readily in hydrofluoric acid producing a corrosive gas-silicon

tetrafluoride.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products should not be

**products:** produced.

## **Section 11. Toxicological information**

## Information on toxicological effects

Acute toxicity: Fly ash LD50/LC50 = Not available

Irritation/Corrosion: Skin: May cause skin irritation. May cause serious burns in the presence of moisture.

**Eyes:** Causes serious eye damage. May cause burns in the presence of moisture.

**Respiratory:** May cause respiratory tract irritation.

Sensitization: May cause sensitization due to the potential presence of trace amounts of hexavalent chromium.

**Mutagenicity:** There are no data available.

Carcinogenicity: Classification below:

Product/ingredient name	OSHA	IARC	ACGIH	NTP
Fly ash, chemicals	-	-	A4	-
Crystalline Silica (Quartz) (CAS 14808-60-7)	Listed	1	A2	Known to be a human carcinogen.

**Reproductive toxicity: There are no data available. There are no data available.**There are no data available.



#### Specific target organ toxicity (single exposure)

Name	Category	Route of Exposure	Target Organs
Calcium oxide	Category 3	Inhalation and skin contact	Respiratory tract irritation, skin irritation
Fly ash, chemicals	Category 3	Inhalation and skin contact	Respiratory tract irritation, skin irritation

#### Specific target organ toxicity (repeated exposure)

Name	Category	Route of Exposure	Target Organs
Crystalline Silica (Quartz) (CAS 14808-60-7)	Category 1	Inhalation	Respiratory tract and kidneys

**Aspiration hazard:** There are no data available.

### Information on the likely routes of exposure

Potential acute health effects: Eye contact: Causes serious eye damage.

Inhalation: May cause respiratory irritation.

Skin contact: Causes severe burns. May cause an allergic skin reaction.

Ingestion: May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics:

**Eye contact:** Adverse symptoms may include the following: pain, watering, redness.

**Inhalation:** Adverse symptoms may include the following: respiratory tract irritation, coughing **Skin contact:** Adverse symptoms may include the following: pain or irritation, redness, blistering may

occur, skin burns, ulcerations and necrosis may occur

Ingestion: Adverse symptoms may include the following: stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure: Short term exposure

Potential immediate effects: No known significant effects or critical hazards. Potential delayed effects: No known significant effects or critical hazards.

#### Long term exposure

Potential immediate effects: No known significant effects or critical hazards. Potential delayed effects: No known significant effects or critical hazards.

Potential chronic health effects:

**General:** Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. If sensitized to hexavalent chromium, a severe allergic dermal reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity:** Fly ash is not classifiable as a human carcinogen. Crystalline silica is considered a hazard by inhalation. IARC has classified crystalline silica as a Group 1 substance, carcinogenic to humans. This classification is based on the findings of laboratory animal studies (inhalation and implantation) and epidemiology studies that were considered sufficient for carcinogenicity. Excessive exposure to crystalline silica can cause silicosis, a non-cancerous lung disease.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

Numerical measures of toxicity:

Acute toxicity estimates: There are no data available.

# **Section 12. Ecological Information**

# **Toxicity**

Product/ingredient name	Result	Species	Exposure
Calcium oxide	Chronic NOEC 100 mg/L Fresh water	Fish-Oreochromis niloticus-Juvenile (Fledgling, Hatchling, Weanling)	46 days



Persistence and degradability: There are not data available. Bioaccumulative potential: There are not data available.

Mobility in soil:Soil/water partition coefficient (Koc): Not available.Other adverse effects:No known significant effects or critical hazards.

## **Section 13. Disposal considerations**

Disposal methods:

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Untreated waste should not be released to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe manner. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff, and contact with soil, waterways, drains and sewers.

# **Section 14. Transportation information**

	DOT Classification	IMDG	IATA
UN number	Not regulated	Not regulated	Not regulated
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	None	None	None
Canada TDG	-	-	-
Additional information	-	-	-

Special precautions for

user:

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. Not available.

# **Section 15. Regulatory Information**

TSCA 6 final risk management: Chromium, ion (Cr6+)

United States inventory (TSCA 8b): Fly ashs are considered to be statutory mixtures under TSCA. CAS 65997-15-1 is included on the TSCA inventory.

CERCLA: This product is not listed as a CERCLA substance

Clean Air Act Section 112 (b): Hazardous Air Pollutants (HAPs) - Not listed

Clean Air Act Section 602: Class I Substances - Not listed Clean Air Act Section 602: Class II Substances - Not listed DEA List I Chemicals: (Precursor Chemicals) - Not listed DEA List II Chemicals: (Essential Chemicals) - Not listed

Canada NSNR Status - Listed on DSL or exempt

#### **SARA 311/312**

Classification: Immediate (acute) health hazard Delayed (chronic) health hazard

#### Composition/information on ingredients

Name	%	Fire Hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Calcium oxide	0-5	No	No	No	Yes	No
Quartz	>0.1	No	No	No	No	Yes
Chromium, ion (Cr6+)	<0.1	No	No	No	Yes	Yes

#### **SARA 313**

	Product name	CAS number	%
Form R-Report requirements	Chromium, ion (Cr6+)	8540-29-9	<0.1

## State regulations

Massachusetts: The following components are listed: fly ash, chemicals

**New York:** None of the components are listed.

New Jersey: The following components are listed: fly ash, chemicals Pennsylvania: The following components are listed: fly ash, chemicals

## California Prop. 65

WARNING: This product contains crystalline silica and chemicals (trace metals) known to the State of California to cause cancer, birth defects or other reproductive harm. California law requires the above warning in the absence of definitive testing to prove the defined risks do not exist.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Quartz	Yes	No	No	No
Chromium, ion (Cr6+)	Yes	Yes	0.001µg/day (inhalation)	8.2 micrograms/day (ingestion)

## International regulations

International lists: Canadian Domestic Substances List (DSL): Fly ash is included on the DSL.

Mexico Inventory (INSQ): All components are listed or exempted.

WHMIS Classification: D2A "Materials Causing Other Toxic Effects"



# **Section 16.** Other Information

**Date of issue:** 09/01/2023

Replaces:

Revised Section(s):

#### Notice to reader

While the information provided in this safety data sheet is believed to provide a useful summary of the hazards of fly ash as it is commonly used, the sheet cannot anticipate and provide all of the information that might be needed in every situation. Inexperienced product users should obtain proper training before using this product. In particular, the data furnished in this sheet do not address hazards that may be posed by other materials mixed with fly ash to produce fly ash products. Users should review other relevant material safety data sheets before working with this fly ash or working on fly ash products, for example, fly ash concrete.

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY Heidelberg Materials, except that the product shall conform to contracted specifications. The information provided herein was believed by the Heidelberg Materials to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information to comply with all laws and procedures applicable to the safe handling and use of product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for non-delivery of product, and whether based on contract, breach of warranty, negligence, or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.

### **Abbreviations**

ACGIH — American Conference of Governmental Industrial Hygienists

CAS — Chemical Abstract Service

CERCLA — Comprehensive Emergency Response and Comprehensive Liability Act

CFR — Code of Federal Regulations

DOT — Department of Transportation

GHS — Globally Harmonized System

HEPA — High Efficiency Particulate Air

IATA — International Air Transport Association
IARC — International Agency for Research on Cancer
IMDG — International Maritime Dangerous Goods

NIOSH — National Institute of Occupational Safety and Health

NOEC — No Observed Effect Concentration

NTP — National Toxicology Program

OSHA — Occupational Safety and Health Administration

PEL — Permissible Exposure Limit
REL — Recommended Exposure Limit

RQ — Reportable Quantity

SARA — Superfund Amendments and Reauthorization Act

SDS — Safety Data Sheet

TLV — Threshold Limit Value

TPQ — Threshold Planning Quantity

TSCA — Toxic Substances Control Act TWA — Time-Weighted Average

UN — United Nations